

# FT-197 Navonna Fountain

**Three people are recommended for the installation of this fountain!**



## Pump Kit Parts List

PK500 Pump (1)  
#10 stopper (1)  
Approx. 24" length of 1/2" black non-kink tubing (1) \*\*  
Approx. 2" length of 5/8" clear vinyl tubing (1) \*\*  
Approx. 2" length of 1/2" CPVC pipe (1) \*\*  
Approx. 12" length of 1/2" black non-kink tubing (1) \*\*  
Approx. 2" length of 5/8" clear vinyl tubing (2) \*\*  
Approx. 2" length of 1/2" CPVC pipe (1) \*\*  
Hose clamps (1) \*  
Wedges (3)  
#7 Drain Stopper (1)

\* Hose clamps may be used as flow restrictors  
\*\* Tubing has been preassembled

### FOUNTAIN INFORMATION:

**This fountain holds approximately 37-40 gallons of water.**

**This fountain uses a medium fountain cover but does not cover the basin.  
(FTNCOV-MED)**

**Compatible with #10 Refill Device and LED kits  
(A special stopper is required to use the refill kit for this fountain.)**

### TOOLS REQUIRED:

Bubble Level



### PUMP INFORMATION:

**OEMPF525 - 525 GPH Pump  
16 FT cord length**

## - W I N T E R   C A R E -

Fountain bowls/tops and other fountain components, which collect water, should not be left outside in the winter since any component, which fills with water and freezes may crack. Likewise, components such as pedestals, which remain in a basin, filled with water, which then freezes, may also crack or crumble. Ideally, therefore, a fountain should always be stored indoors or in a dry protected place such as a covered porch away from the elements. However, if a fountain must be left outside:

- (1) Remove pump, rubber stoppers, drainpipes, finials, and other small components for storage indoors. Note that stoppers or drainpipes are removed to allow drainage in the event water accumulates in any basin.
- (2) Raise fountain base from ground with wood strips so that base will not freeze to the ground surface.
- (3) Cover or wrap the fountain with burlap or other absorbent material (old blanket or towel) and then cover securely with plastic, making sure that water will not accumulate in the basin or other fountain component and freeze;
- (4) Check fountain periodically to ensure that plastic is secure and water is not accumulating in any fountain component.

## - G E N E R A L   F O U N T A I N   T I P S -

**Install fountains on a level surface.** You will need a properly grounded 110-volt (AC only) GFCI protected receptacle near the fountain for your pump. All pumps are submersible and must be completely underwater to function properly. Test all pumps and adjust to full output prior to assembly. It is not recommended that fountains be placed directly on grass or dirt. Position the channel opening at the base of each fountain toward the electrical outlet to be used since the pump cord will be threaded through this opening.

Check out YouTube for a "How to" video.  
For more Campania product information visit [www.campaniainternational.com](http://www.campaniainternational.com)

All of our cast stone is proudly



Made in USA


# FT-197 Navonna Fountain

## Three people are recommended for the installation of this fountain!


Assemble your fountain on a level surface capable of holding a minimum of 1286 pounds with an approximate 17.5 square foot footprint.




FT-197F (720 lbs)  
56.5"L x 56.5"W x 11.5"H




FT-197D (67 lbs)  
12.75"L x 12.75"W x 10"H




FT-197C (43 lbs)  
11"L x 11"W x 8.5"H



FT-197B (89 lbs)  
20.5"W x 18.5"H



FT-197A (19 lbs)  
15.75"W x 3"H



FT-197E (8 lbs)  
7"L x 2.5"W x 5"H

1. Place the basin (FT-197F) into position where the fountain will be installed, ensuring that it is level.
  - a. **Be sure to check that each part is level and centered during the assembly of this fountain.**
2. Assemble the pump kit
  - a. Using a hose clamp, attach the 24" length of 1/2" non-kink tubing to the pump outlet.
  - b. Place the stopper around the pump cord about 12" from the pump.
3. Feed the pump cord through the hole and channel in the basin (FT-197F).
4. **FIRMLY** press the stopper into the hole evenly.
  - a. **Note:** Using the handle of a screwdriver or hammer works best.
5. Place the pump house (FT-197D) over the pump and in the center of the basin (FT-197F).
6. Place the pedestal (FT-197C) over the pump house (FT-197D).

### **BOTTOM OF URN (FT-197B)**

7. Position the urn (FT-197B) over the pedestal (FT-197C).
8. Insert the CPVC pipe already connected to the 24" tubing assembly into the CPVC coupling in the bottom of the urn (FT-197B).
9. Center the urn (FT-197B) on the pedestal (FT-197C).

### **INSIDE OF URN (FT-197B)**

10. Slip the 5/8" clear end of the 12" tubing assembly over the CPVC pipe protruding from the bottom center of the urn.
11. Position the water feature disc (FT-197A) over the urn (FT-197B).
12. Insert the CPVC pipe already connected to the 12" tubing assembly into the CPVC coupling in the bottom of the disc (FT-197A).
13. Center the disc (FT-197A) in the urn (FT-197B).
14. Fit the pump house door (FT-197E) into the pump house (FT-197D).
15. Insert the #7 Drain stopper into the drain hole next to the outer wall of the basin (FT-197F).
16. Fill the fountain with water.