

FT-223 Carrera Fountain

Two people are required for the installation of this fountain!



Pump Kit Parts List

PK 300 Pump (1)
#10 stopper (1)
18" length of 1/2" Black Non-Kink tubing (1) **
3" length of 5/8" clear tubing (1) **
Wedges (4)
Copper Spillers (4) 2 of each size
2.8 oz tube of 100% clear silicone
Hose clamps (3) *

* Hose clamps may be used as flow restrictors
** Tubing has been preassembled

FOUNTAIN INFORMATION:


This fountain holds approximately 17 gallons of water.

**This fountain uses a medium fountain cover.
(FTNCOV-MED)**

**Compatible with Refill #10 Device
(A different style stopper may be requested for this part.)**

TOOLS REQUIRED:

Bubble Level



PUMP INFORMATION:

**OEMPF320 - 320 GPH Pump
16 FT cord length**

- WINTER CARE -

Fountain bowls/tops and other fountain components, which collect water, should not be left outside in the winter since any component, which fills with water and freezes may crack. Likewise, components such as pedestals, which remain in a basin, filled with water, which then freezes, may also crack or crumble. Ideally, therefore, a fountain should always be stored indoors or in a dry protected place such as a covered porch away from the elements. However, if a fountain must be left outside:

- (1) Remove pump, rubber stoppers, drainpipes, finials, and other small components for storage indoors. Note that stoppers or drainpipes are removed to allow drainage in the event water accumulates in any basin.
- (2) Raise fountain base from ground with wood strips so that base will not freeze to the ground surface.
- (3) Cover or wrap the fountain with burlap or other absorbent material (old blanket or towel) and then cover securely with plastic, making sure that water will not accumulate in the basin or other fountain component and freeze;
- (4) Check fountain periodically to ensure that plastic is secure and water is not accumulating in any fountain component.

- GENERAL FOUNTAIN TIPS -

Install fountains on a level surface. You will need a properly grounded 110-volt (AC only) GFCI protected receptacle near the fountain for your pump. All pumps are submersible and must be completely underwater to function properly. Test all pumps and adjust to full output prior to assembly. It is not recommended that fountains be placed directly on grass or dirt. Position the channel opening at the base of each fountain toward the electrical outlet to be used since the pump cord will be threaded through this opening.

All of our cast stone is proudly




Check out YouTube for a "How to" video.

For more Campania product information visit www.campaniainternational.com


FT-223 Carrera Fountain

Two people are required for the installation of this fountain!


Assemble your fountain on a level surface capable of holding a minimum of 420 pounds with an approximate 1.25 square foot footprint




FT-223E (167 lbs)
39.5"L x 28.25"W x 15.25"H




FT-223C (70 lbs)
25.5"L x 18.25"W x 12.5"H



FT-223B (27 lbs)
16.5"L x 12"W x 9.75"H



FT-223A (1 lb)
5.5"L x 4"W x 2.25"H



FT-223D (1 lb)
4.75"L x 2"W x 4.5"H

1. Place the Basin (FT-223E) into position where the fountain is to be installed.
2. Assemble the pump kit
 - a. **NOTE: All pumps come with 1 adapter already inserted into the pump and 2 adapters secured to the power cord.**
 - i. **This fountain uses the medium adapter provided.**
 - b. Using a hose clamp, secure the non-kink tubing to the pump outlet.
 - c. Place the stopper around the pump cord approximately 8" from the pump.
3. Feed the pump cord all the way through the hole and channel in the basin (FT-132F).
4. **FIRMLY** press the stopper into the hole evenly.
 - a. Note: Using the handle of a screwdriver or hammer works best to press the stopper in place.
5. Center the middle bowl (FT-223C) over the basin (FT-223E).
6. Slide the 5/8" clear end of the tubing assembly over pipe protruding from the bottom of the middle bowl (FT-223C).
7. Use a small amount of the silicone provided to secure the larger spillers to the middle bowl (FT-223C).
8. Place the small top bowl with pedestal (FT-223B) into the middle bowl by placing it over the pipe protruding up inside the bowl and ensure that it is level.
9. Use a small amount of the silicone provided to secure the smaller spillers to the top bowl (FT-223B).
10. Place the water cap (FT-223A) over the pipe protruding up from the top small bowl.
11. Place the Pump Cover Door (FT-223D) in the pump window of the middle bowl.
12. Let the fountain sit 24 hours before filling.