

FT-225 Longvue Fountain

Two people are recommended for the installation of this fountain!



FOUNTAIN INFORMATION:

This fountain holds approximately 10 gallons of water.

**This fountain uses an extra-large fountain cover.
(FTNCOV-XLG)**

**This fountain is compatible with a LED kit.
(A special stopper is not required for this part.)**

Pump Kit Parts List

PK300 pump (1)
#10 stopper (1)
Approx. 24" length of ½" black non-kink tubing (1)
Wedges (4)
Hose clamps (3) *

* Hose clamps may be used as flow restrictors

TOOLS REQUIRED:

Bubble Level



PUMP INFORMATION:

**OEMPF320 - 320 GPH Pump
16 FT cord length**

- W I N T E R C A R E -

Fountain bowls/tops and other fountain components, which collect water, should not be left outside in the winter since any component, which fills with water and freezes may crack. Likewise, components such as pedestals, which remain in a basin, filled with water, which then freezes, may also crack or crumble. Ideally, therefore, a fountain should always be stored indoors or in a dry protected place such as a covered porch away from the elements. However, if a fountain must be left outside:

- (1) Remove pump, rubber stoppers, drainpipes, finials, and other small components for storage indoors. Note that stoppers or drainpipes are removed to allow drainage in the event water accumulates in any basin.
- (2) Raise fountain base from ground with wood strips so that base will not freeze to the ground surface.
- (3) Cover or wrap the fountain with burlap or other absorbent material (old blanket or towel) and then cover securely with plastic, making sure that water will not accumulate in the basin or other fountain component and freeze;
- (4) Check fountain periodically to insure that plastic is secure and water is not accumulating in any fountain component.

- G E N E R A L F O U N T A I N T I P S -

Install fountains on a level surface. You will need a properly grounded 110-volt (AC only) GFCI protected receptacle near the fountain for your pump. All pumps are submersible and must be completely underwater to function properly. Test all pumps and adjust to full output prior to assembly. It is not recommended that fountains be placed directly on grass or dirt. Position the channel opening at the base of each fountain toward the electrical outlet to be used since the pump cord will be threaded through this opening.

All of our cast stone is proudly



Made in USA


Check out YouTube for a "How to" video.

For more Campania product information visit www.campaniainternational.com


FT-225 Longvue Fountain

Two people are recommended for the installation of this fountain!


Assemble your fountain on a level surface capable of holding a minimum of 630 pounds with an approximate 1.75 square foot footprint.




FT-225F (224 lbs)
16.25"L x 16.25"W x 24.5"H




FT-239E (210 lbs)
36.5"W x 10"H




FT-225C (39 lbs)
10"W x 13"H



FT-225B (56 lbs)
21.5"W x 6.75"H



FT-225A (11 lbs)
5.5"W x 11"H



FT-225D (2 lbs)
5.5"L x 1.5"W x 3.5"H

1. Place the base (FT-225F) into position where the fountain will be installed, ensuring that it is level.
2. Assemble the pump kit
 - a. Attach the non-kink tubing to the pump outlet.
 - b. Place the stopper around the pump cord about 6" from the pump.
3. Center the large bowl (FT-239E) over the base (FT-225F).
4. Feed the pump cord through the hole in the large bowl (FT-239E) and the channel in the base (FT-225F).
5. **FIRMLY** press the stopper into the hole evenly.
 - a. **Note:** Using the handle of a screwdriver or hammer works best.
6. Place the pump house (FT-225C) over the pump and in the center of the large bowl (FT-239E).
7. Feed the non-kink tubing through the top of the pump house (FT-225C).
8. Center the small bowl (FT-225B) over the pump house (FT-225C).
9. Use a hose clamp to secure the loose end of the non-kink tubing to the pipe protruding from the bottom of the small bowl (FT-225B).
10. Center the finial (FT-225A) over the small bowl (FT-225B).
11. Fit the pipe protruding from the top of the small bowl (FT-225B) into the hole in the bottom of the finial (FT-225A).
12. Fit the pump house door (FT-225D) into the pump house (FT-225C).
13. Fill the fountain with water.