

FT-247 Equinox Birdbath Fountain



FOUNTAIN INFORMATION:

This fountain holds approximately 4 gallons of water.

**This fountain uses a small fountain cover.
(FTNCOV-SM)**

**Not recommended for use with refill kits or LED
light kits.**

Pump Kit Parts List

PK140 pump (1)
#10 stopper (1)
Approx. 6" length of 1/2" black non-kink tubing (1) **
Approx. 2" length of 5/8" clear tubing (1) **
Approx. 2" length of 1/2" CPVC pipe (1) **
Hose clamps (1) *
Wedges (2)

*Hose clamps may be used as flow restrictors

**Black non-kink tubing and clear vinyl tubing have been preassembled

TOOLS REQUIRED:

Bubble Level



PUMP INFORMATION:

**PF140 - 140 GPH Pump
6 FT cord length**

- W I N T E R C A R E -

Fountain bowls/tops and other fountain components, which collect water, should not be left outside in the winter since any component, which fills with water and freezes may crack. Likewise, components such as pedestals, which remain in a basin, filled with water, which then freezes, may also crack or crumble. Ideally, therefore, a fountain should always be stored indoors or in a dry protected place such as a covered porch away from the elements. However, if a fountain must be left outside:

- (1) Remove pump, rubber stoppers, drainpipes, finials, and other small components for storage indoors. Note that stoppers or drainpipes are removed to allow drainage in the event water accumulates in any basin.
- (2) Raise fountain base from ground with wood strips so that base will not freeze to the ground surface.
- (3) Cover or wrap the fountain with burlap or other absorbent material (old blanket or towel) and then cover securely with plastic, making sure that water will not accumulate in the basin or other fountain component and freeze;
- (4) Check fountain periodically to ensure that plastic is secure and water is not accumulating in any fountain component.

- G E N E R A L F O U N T A I N T I P S -

Install fountains on a level surface. You will need a properly grounded 110-volt (AC only) GFCI protected receptacle near the fountain for your pump. All pumps are submersible and must be completely underwater to function properly. Test all pumps and adjust to full output prior to assembly. It is not recommended that fountains be placed directly on grass or dirt. Position the channel opening at the base of each fountain toward the electrical outlet to be used since the pump cord will be threaded through this opening.

All of our cast stone is proudly



Made in USA

Check out YouTube for a "How to" video.

For more Campania product information visit www.campaniainternational.com


FT-247 Equinox Birdbath Fountain

Assemble your fountain on a level surface capable of holding a minimum of 70 pounds with an approximate 8 square inch footprint.



FT-246B (116 lbs)
20.5"W x 30.25"H

1. Position the base (FT-246B) where the fountain is to be installed, ensuring that it is level.
2. Assemble the pump kit
 - a. Using a hose clamp, connect the 1/2" non-kink tubing to the pump.
 - b. Place the stopper around the pump cord approximately 3-5" from the pump.
3. Feed the pump cord through the base (FT-246B) until the stopper reaches the hole.
 - a. Be sure the cord is fed through the channel at the bottom of the base.
4. **FIRMLY** press the stopper into the hole evenly.
 - a. Note: Using the handle of a screwdriver or hammer works best to press the stopper in place.



FT-247A (16 lbs)
16.75"W x 1"H

5. Insert the CPVC pipe connected to the tubing and pump into the CPVC coupling on the bottom of the water feature disc (FT-247A).
 6. Center and level the disc (FT-247A).
-
7. Fill the fountain with water.